

SEVERE DUTY LOADER ROCK BUCKET

RECOMMENDED APPLICATIONS:

Specifically designed to penetrate severe digging applications or re-handle loose rock.

QUALITY CONSTRUCTION:

High strength, T-1 steel is utilized in all critical wear points of the bucket. Abrasion-resistant steel is used in wear-straps to reinforce bottom of bucket.

STANDARD SIZES AVAILABLE:

2 cu. yd to 10.0 cu. yd. Widths range from 100" - 144".
Other capacities and widths are available upon quotation.
Available in spade nose and straight edge options.

ADDITIONAL FEATURES:

Available with replaceable bolt-on cutting edge upon request. Weld-on teeth are standard equipment. Other tooth selections available. Easily mounts up to Werk-Brau front coupler or available with pin-up connection. Special designs and capacities are available, please request a quote from a Dealer or contact Werk-Brau directly.



***Spade Lip shown

CONTINUED ON NEXT PAGE

SEVERE DUTY LOADER ROCK BUCKET

SEVERE DUTY ROCK LOADER BUCKET

LOADER CLASS	PART NUMBER	BUCKET WIDTH	EDGE LENGTH	NO. OF TEETH	CAPACITY STRUCK	CAPACITY RATED	WEIGHT
1	WL1R100-2.00	100"	102"	7	1.69	2.00	2500
1	WL1R100-2.00SP	100"	102"	7	1.69	2.00	2800
1	WL1R100-2.50	100"	102"	7	2.17	2.50	2700
1	WL1R100-2.50SP	100"	102"	7	2.17	2.50	3000
2 & 3	WL3R100-2.50	100"	102"	7	2.17	2.50	2700
2 & 3	WL3R100-2.50SP	100"	102"	7	2.17	2.50	3000
2 & 3	WL3R100-3.00	100"	102"	7	2.54	3.00	3500
2 & 3	WL3R100-3.00SP	100"	102"	7	2.54	3.00	3900
3.5	WL3.5R105-3.00	105"	108"	8	2.54	3.00	4200
3.5	WL3.5R105-3.00SP	105"	108"	8	2.54	3.00	4600
3.5	WL3.5R105-3.50	105"	108"	8	2.97	3.50	4600
3.5	WL3.5R105-3.50SP	105"	108"	8	2.97	3.50	5000
4	WL4R117-4.00	117"	119"	8	3.30	4.00	4600
4	WL4R117-4.00SP	117"	119"	8	3.30	4.00	5200
4	WL4R117-4.50	117"	119"	8	3.81	4.50	5200
4	WL4R117-4.50SP	117"	119"	8	3.81	4.50	5500
5	WL5R124-4.75	124"	126"	8	3.95	4.75	6100
5	WL5R124-4.75SP	124"	126"	8	3.95	4.75	6500
5	WL5R124-5.50	124"	126"	8	4.60	5.50	6500
5	WL5R124-5.50SP	124"	126"	8	4.60	5.50	6900
5	WL5R124-6.25	124"	126"	8	5.30	6.25	7400
5	WL5R124-6.25SP	124"	126"	8	5.30	6.25	7900
6	WL6R138-6.50	138"	140"	9	5.51	6.50	8000
6	WL6R138-6.50SP	138"	140"	9	5.51	6.50	8500
6	WL6R138-7.50	138"	140"	9	6.36	7.50	9300
6	WL6R138-7.50SP	138"	140"	9	6.36	7.50	9800
7	WL7SD144-8	144"	147"	9	7.00	8.00	13500
7	WL7SD144-8SP	144"	147"	9	7.00	8.00	14000
7	WL7R144-9.00	144"	147"	9	8.00	9.00	14200
7	WL7R144-9.00SP	144"	147"	9	8.00	9.00	14700
7	WL7R144-10	144"	147"	9	9.00	10.00	15000
7	WL7R144-10SP	144"	147"	9	9.00	10.00	15500