

DITCHING AND GRADING BUCKET

RECOMMENDED APPLICATIONS:

Specifically designed for ditch maintenance and construction. Also useful in grading and slope work. For high capacity buckets, use the next weight class up in Ditching Bucket, except long reach machines. Werk-Brau manufactures a severe duty version of this bucket.

QUALITY CONSTRUCTION:

Werk-Brau manufactures this bucket using T-1 steel in all high wear components to ensure that the bucket will have a long operating life. A rigid top section assures structural stability in the wider sizes. The bottom of the bucket is reinforced with wear straps. Each bucket is engineered with tapered side plates to reduce wear on the buckets sides, and to allow for easier dumping.

STANDARD SIZES AVAILABLE:

Standard widths range from 48" - 84", and capacities of .64 cu. yd. - 3.81 cu. yd.

ADDITIONAL FEATURES:

Werk-Brau recommends a bolt-on cutting edge to extend and protect the bucket edge for extended hours of operation. Additional drain holes are available, for aquatic applications, Werk-Brau offers an Aquatic Ditching Bucket. Special designs and capacities are available, please request a quote from a dealer or contact Werk-Brau directly.



CONTINUED ON NEXT PAGE

DITCHING AND GRADING BUCKET

DITCHING AND GRADING BUCKET

METRIC TON CLASS	PART NUMBER	BUCKET WIDTH	BUCKET CUT	CAPACITY STRUCK	CAPACITY RATED	WEIGHT
Long Reach	1DCG48	48"	49"	0.58	0.64	950
Long Reach	1DCG54	54"	55"	0.60	0.73	1,000
Long Reach	1DCG60	60"	60"	0.73	1.02	1,100
12, 15 & 20	1DCG48	48"	49"	0.58	0.64	950
12, 15 & 20	1DCG54	54"	54"	0.65	0.73	1,000
12, 15 & 20	1DCG60	60"	60"	0.73	1.02	1,100
12, 15 & 20	1DCG66	66"	66"	0.80	1.12	1,200
12, 15 & 20	1DCG72	72"	72"	0.87	1.22	1,300
12, 15 & 20	1DCG78	78"	72"	0.98	1.32	1,350
25	2DCG48	48"	49"	0.80	1.08	1,450
25	2DCG54	54"	55"	0.90	1.23	1,600
25	2DCG60	60"	61"	1.00	1.38	1,650
25	2DCG66	66"	67"	1.10	1.52	1,750
25	2DCG72	72"	73"	1.30	1.77	1,850
25	2DCG78	78"	79"	1.40	2.02	2,000
30	3DCG54	54"	56"	1.13	1.53	2,000
30	3DCG60	60"	62"	1.25	1.71	2,150
30	3DCG66	66"	68"	1.38	1.90	2,300
30	3DCG72	72"	74"	1.51	2.09	2,450
30	3DCG84	84"	85"	1.77	2.47	2,750
35	4DCG54	54"	56"	1.24	1.67	2,600
35	4DCG60	60"	62"	1.38	1.88	2,450
35	4DCG66	66"	68"	1.51	2.07	2,625
35	4DCG72	72"	74"	1.61	2.28	2,800
35	4DCG78	78"	80"	1.79	2.49	2,950
35	4DCG84	84"	86"	1.97	2.70	3,150
40	5DCG60	60"	62"	1.48	2.01	3,100
40	5DCG66	66"	68"	1.63	2.24	3,275
40	5DCG72	72"	74"	1.78	2.46	3,500
40	5DCG78	78"	78"	1.92	2.67	3,725
40	5DCG84	84"	84"	2.07	2.89	3,875
50	6DCG60	60"	62"	1.78	2.40	3,725
50	6DCG66	66"	66"	1.95	2.68	3,925
50	6DCG72	72"	74"	2.13	2.92	4,175
50	6DCG78	78"	80"	2.31	3.19	4,375
50	6DCG84	84"	86"	2.84	3.81	4,350