

EXTREME DUTY BUCKETS

RECOMMENDED APPLICATIONS:

Designed with an aggressive dig angle to effectively excavate in the toughest conditions. Ideal applications for this bucket include but are not limited to demolition work, shot rock, high abrasive applications, and moderate prying. When paired with a thumb, this bucket can also be used for material handling.

QUALITY CONSTRUCTION:

T-1 steel is utilized in all critical or high wear components. This bucket features tapered side plates, horizontal wear straps, and an extra thick cutting edge is backed by a wear plate that covers the entire bucket bottom. Side wear plates protect the bucket sides in the high wear areas and extend the buckets operation life.

CUTTING EQUIPMENT OPTIONS:

Equipped with industry standard teeth for extra durability. In most cases, the tooth size is increased to tolerate the more extreme digging application

STANDARD SIZES AVAILABLE:

3/8 cubic yds. to 4 cubic yds. of various widths are available. Special designs and capacities available upon request.

ADDITIONAL FEATURES:

Bolt-on side cutters are highly recommended for added endurance. Box rippers are available and can be installed upon request. Special designs and capacities are available, please request a quote from your local dealer.



25 METRIC TON - 50,000 TO 59,000 LBS

| PART NUMBER | BUCKET WIDTH | BUCKET CUT | CAPACITY STRUCK | CAPACITY RATED | NO. OF TEETH | WEIGHT |
|-------------|--------------|------------|-----------------|----------------|--------------|--------|
| E25ED24 | 24" | 26" | 0.67 | 0.79 | 3 | 2,390 |
| E25ED30 | 30" | 32" | 0.84 | 1.02 | 4 | 2,640 |
| E25ED36 | 36" | 38" | 1.01 | 1.25 | 5 | 2,970 |
| E25ED42 | 42" | 44" | 1.18 | 1.48 | 5 | 3,220 |
| E25ED48 | 48" | 50" | 1.35 | 1.72 | 6 | 3,580 |
| E25ED54 | 54" | 56" | 1.52 | 1.96 | 6 | 3,940 |

CONTINUED ON NEXT PAGE

EXTREME DUTY BUCKETS

30 METRIC TON - 59,000 TO 68,000 LBS

| PART NUMBER | BUCKET WIDTH | BUCKET CUT | CAPACITY STRUCK | CAPACITY RATED | NO. OF TEETH | WEIGHT |
|-------------|--------------|------------|-----------------|----------------|--------------|--------|
| E30ED24 | 24" | 26" | 0.74 | 0.86 | 3 | 2,500 |
| E30ED30 | 30" | 32" | 0.92 | 1.11 | 4 | 2,860 |
| E30ED36 | 36" | 38" | 1.11 | 1.36 | 4 | 3,165 |
| E30ED42 | 42" | 44" | 1.29 | 1.62 | 5 | 3,500 |
| E30ED48 | 48" | 50" | 1.48 | 1.88 | 5 | 3,775 |
| E30ED54 | 54" | 56" | 1.66 | 2.14 | 6 | 4,165 |
| E30ED60 | 60" | 62" | 1.85 | 2.40 | 6 | 4,550 |

35 METRIC TON - 68,000 TO 82,000 LBS

| PART NUMBER | BUCKET WIDTH | BUCKET CUT | CAPACITY STRUCK | CAPACITY RATED | NO. OF TEETH | WEIGHT |
|-------------|--------------|------------|-----------------|----------------|--------------|--------|
| E35ED24 | 24" | 26" | 0.80 | 0.93 | 3 | 2,920 |
| E35ED30 | 30" | 32" | 1.00 | 1.20 | 4 | 3,250 |
| E35ED36 | 36" | 38" | 1.20 | 1.47 | 4 | 3,580 |
| E35ED42 | 42" | 44" | 1.40 | 1.75 | 5 | 4,000 |
| E35ED48 | 48" | 50" | 1.60 | 2.03 | 5 | 4,275 |
| E35ED54 | 54" | 56" | 1.80 | 2.31 | 6 | 4,690 |
| E35ED60 | 60" | 62" | 2.00 | 2.60 | 6 | 4,970 |

40 METRIC TON - 82,000 TO 105,000 LBS

| PART NUMBER | BUCKET WIDTH | BUCKET CUT | CAPACITY STRUCK | CAPACITY RATED | NO. OF TEETH | WEIGHT |
|-------------|--------------|------------|-----------------|----------------|--------------|--------|
| E40ED24 | 24" | 26" | 0.94 | 1.09 | 3 | 3,330 |
| E40ED30 | 30" | 32" | 1.18 | 1.39 | 3 | 3,690 |
| E40ED36 | 36" | 38" | 1.41 | 1.71 | 4 | 4,100 |
| E40ED42 | 42" | 44" | 1.65 | 2.03 | 5 | 4,550 |
| E40ED48 | 48" | 50" | 1.88 | 2.36 | 5 | 4,860 |
| E40ED54 | 54" | 56" | 2.12 | 2.69 | 6 | 5,330 |
| E40ED60 | 60" | 62" | 2.35 | 3.03 | 6 | 5,800 |

CONTINUED ON NEXT PAGE

EXTREME DUTY BUCKETS

55 METRIC TON - 105,000 TO 125,000 LBS

| PART NUMBER | BUCKET WIDTH | BUCKET CUT | CAPACITY STRUCK | CAPACITY RATED | NO. OF TEETH | WEIGHT |
|-------------|--------------|------------|-----------------|----------------|--------------|--------|
| E55ED42 | 42" | 48" | 2.09 | 2.53 | 4 | 6,987 |
| E55ED48 | 48" | 54" | 2.44 | 3 | 5 | 7,599 |
| E55ED54 | 54" | 60" | 2.78 | 3.46 | 5 | 8,060 |
| E55ED60 | 60" | 66" | 3.12 | 4 | 5 | 8,507 |
| E55ED66 | 66" | 72" | 3.46 | 4.42 | 6 | 9,120 |
| E55ED72 | 72" | 78" | 3.8 | 4.9 | 6 | 10,640 |

65 METRIC TON - 125,000 TO 150,000 LBS

| PART NUMBER | BUCKET WIDTH | BUCKET CUT | CAPACITY STRUCK | CAPACITY RATED | NO. OF TEETH | WEIGHT |
|-------------|--------------|------------|-----------------|----------------|--------------|--------|
| E65ED42 | 42" | 48" | 2.29 | 2.75 | 4 | 7,200 |
| E65ED48 | 48" | 54" | 2.66 | 3.24 | 5 | 7,800 |
| E65ED54 | 54" | 60" | 3.03 | 3.75 | 5 | 8,267 |
| E65ED60 | 60" | 66" | 3.41 | 4.27 | 6 | 8,867 |
| E65ED66 | 66" | 72" | 3.78 | 4.79 | 6 | 9,294 |
| E65ED72 | 72" | 78" | 4.15 | 5.31 | 6 | 9,734 |
| E65SD84 | 84" | 89" | 4.83 | 6.27 | 6 | 10,134 |

75 METRIC TON - 154,000 TO 180,000 LBS

| PART NUMBER | BUCKET WIDTH | BUCKET CUT | CAPACITY STRUCK | CAPACITY RATED | NO. OF TEETH | WEIGHT |
|-------------|--------------|------------|-----------------|----------------|--------------|--------|
| E75ED54 | 54" | 61" | 3.16 | 3.88 | 4 | 9,250 |
| E75ED60 | 60" | 67" | 3.56 | 4.43 | 5 | 10,015 |
| E75ED66 | 66" | 73" | 3.96 | 5 | 5 | 10,550 |
| E75ED72 | 72" | 79" | 4.36 | 5.54 | 5 | 11,080 |
| E75ED78 | 78" | 85" | 4.75 | 6.1 | 6 | 11,850 |
| E75ED84 | 84" | 91" | 5.12 | 6.65 | 6 | 12,370 |

CONTINUED ON NEXT PAGE

EXTREME DUTY BUCKETS

85 METRIC TON - 176,000 TO 200,000 LBS

| PART NUMBER | BUCKET WIDTH | BUCKET CUT | CAPACITY STRUCK | CAPACITY RATED | NO. OF TEETH | WEIGHT |
|-------------|--------------|------------|-----------------|----------------|--------------|--------|
| E85ED54 | 54" | 61" | 3.57 | 4.38 | 4 | 10,774 |
| E85ED60 | 60" | 67" | 4.02 | 5 | 5 | 11,629 |
| E85ED66 | 66" | 73" | 4.57 | 5.63 | 5 | 12,172 |
| E85ED72 | 72" | 79" | 4.91 | 6.27 | 5 | 12,714 |
| E85ED78 | 78" | 85" | 5.36 | 6.9 | 6 | 13,515 |
| E85SD80 | 80" | 87" | 5.51 | 7.12 | 6 | 13,732 |
| E85ED84 | 84" | 91" | 5.81 | 7.54 | 6 | 14,071 |

CONTINUED ON NEXT PAGE