

PAVEMENT REMOVAL BUCKET

RECOMMENDED APPLICATIONS:

Werk-Brau's Pavement Removal Bucket is specifically engineered for removal, handling, and loading of slabs of material such as sidewalks or street. The distinct shape of this bucket makes it easy to wedge under a slab of material to pry it up away from the ground in one or more pieces. The inclined sides of the Bucket aid in prying the pavement or cement free. Not designed for normal dirt excavation or digging. This Bucket can be paired with a thumb.

QUALITY CONSTRUCTION:

T-1 steel is utilized in all critical or high wear components to ensure that this pavement removal bucket has a long operation life. The entire bottom is "ribbed" on the inside to prevent denting and reduce wear.

TOOTH EQUIPMENT OPTIONS:

Equipped with industry standard teeth for extra durability. A selection of high quality brand teeth are available to choose from.

STANDARD SIZES AVAILABLE:

Widths range from 18" to 26" for mini excavators and 24" to 54" for full-size excavators. Special widths available upon request.

ADDITIONAL FEATURES:

Different teeth styles are available.



CONTINUED ON NEXT PAGE

PAVEMENT REMOVAL BUCKET

EXCAVATOR

MACHINE CLASS	PART NUMBER	WIDTH	NO. OF TOOTH	STYLE OF TOOTH	THROAT FRONT-BACK	WEIGHT
12 & 15	12PRB24	24"	3	9W8452	19" - 14"	1,900
12 & 15	12PRB36	36"	3	9W8452	19" - 14"	2,100
12 & 15	12PRB42	42"	4	9W8452	15" - 10"	2,500
20, 25, 30 & 35	20PRB36	36"	3	9W8452	15" - 10"	2,100
20, 25, 30 & 35	20PRB42	42"	4	9W8452	15" - 10"	2,500
20, 25, 30 & 35	20PRB48H	48"	4	9W8452	15" - 10"	3,100
40 & 50	40PRB54H	54"	4	9W8552	20" - 14"	4,800

MINI EXCAVATOR

MACHINE CLASS	PART NUMBER	WIDTH	NO. OF TOOTH	STYLE OF TOOTH	WEIGHT
1 & 15	PRB118	18"	3	8330	275
1 & 15	PRB124	24"	4	8330	370
2	PRB218	18"	3	8330	400
2	PRB224	24"	4	8330	600
3, 4, U1 & U2	PRB324	24"	4	6Y3222	750
3, 4, U1 & U2	PRB336	36"	5	6Y3222	835
5	PRB424	24"	4	6Y3222	750
5	PRB436	36"	4	6Y3222	950